



EB/RF 2-3-4PA



Refrigerated pastry counter, with controlled humidity

The EB/RF are ventilated refrigerated counters, equipped with an exclusive, patented electronic temperature and humidity control system that guarantees optimal conditions for storing all pastry specialties. The EB/RF counters are designed to use 400x600 mm trays, are available in TN versions for fresh pastries (temperature range -2/+10°C) and can be set up in two-, three-, or four-module/door configurations, with a splashback.

Features

Refrigerated counters with ventilated refrigeration, designed to operate in climate class 5 (tropical environments). Equipped with an easily removable monoblock unit for maintenance or replacement. Cataphoretic-treated evaporator with digitally controlled automatic defrosting. Condensation evaporation occurs via a corrosion-resistant coil made of low-carbon AISI 316 stainless steel.

Construction

The doors feature a self-closing mechanism with a fixed 100° lock in the open position, while the seven-chamber magnetic seal is easily removable. A capacitive touchscreen completes the package. The AISI 304 stainless steel feet are adjustable, as are the easily removable rails and racks, also made of AISI 304 stainless steel.

RETARDER PROOFING TABLE	EB/RF 2P RA	EB/RF 3P RA	EB/RF 4P RA
Interior fittings	AISI 304 stainless steel guides and racks - Adjustable and removable.	AISI 304 stainless steel guides and racks - Adjustable and removable.	AISI 304 stainless steel guides and racks - Adjustable and removable.
Grills included	N.1 x door - EN 600x400 - Plasticized	N.1 x door - EN 600x400 - Plasticized	N.1 x door - EN 600x400 - Plasticized
LED strip	not available	not available	not available
WiFi/Bluetooth kit	<input type="checkbox"/> €	<input type="checkbox"/> €	<input type="checkbox"/> €
Key lock	not available	not available	not available
Air distribution duct	not available	<input type="checkbox"/> €	▪
Front-removable motor	<input type="checkbox"/> €	<input type="checkbox"/> €	<input type="checkbox"/> €
Wheel kit	<input type="checkbox"/> €	<input type="checkbox"/> €	<input type="checkbox"/> €
Cable with Schuko or UK plug	▪ (Schuko)	▪ (Schuko)	▪ (Schuko)
▪ Standard <input type="checkbox"/> Optional <input type="checkbox"/> € Paid Optional			




Technical features

MODELS:

EB/RF2PA

EB/RF3PA

EB/RF4PA



TECHNICAL DATA

		EB/RF2P A MOD. WITH 2 DOORS with upstand		EB/RF3P A MOD. WITH 3 DOORS with upstand		EB/RF4P A MOD. WITH 4 DOORS with upstand
		R (refrigerator)	F (freezer)	R (refrigerator)	F (freezer)	R (refrigerator)
Capacity		N.9 (step 55 mm) x door - EN 600x400	N.9 (step 55 mm) x door - EN 600x400	N.9 (step 55 mm) x door - EN 600x400	N.9 (step 55 mm) x door - EN 600x400	N.9 (step 55 mm) x door - EN 600x400
Pairs of guides	n°/No.	included N.1 "L" x door - EN 600x400	included N.1 "L" x door - EN 600x400	included N.1 "L" x door - EN 600x400	included N.1 "L" x door - EN 600x400	included N.1 "L" x door - EN 600x400
Dimensions WxDxH	mm	1430x800x850-1000	1430x800x850-1000	1955x800x850-1000	1955x800x850-1000	2480x800x850-1000
Packaging WxDxH	mm	1470x830x1100	1470x830x1100	1995x830x1100	1995x830x1100	2520x830x1100
Net weight	kg	106	108	136	138	270
Gross weight	kg	127	129	172	164	302
Temperature	°C	(-2/+10)	(-22/-18)	(-2/+10)	(-22/-18)	(-2/+10)
Energy class		A	E	A	E	B
Gross volume	L	388	388	593	593	798
Net volume refrigeration (R)/freezing (F)	L	260	260	389	389	519
Climate class		5 (+40°C / 40% R.H.)	5 (+40°C / 40% R.H.)	5 (+40°C / 40% R.H.)	5 (+40°C / 40% R.H.)	5 (+40°C / 40% R.H.)
Refrigerant gas		R290	R290	R290	R290	R290
Defrosting		ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
Evaporation and condensation		Condensate evaporation via corrosion-resistant coil in AISI 316 low carbon steel	Condensate evaporation via corrosion-resistant coil in AISI 316 low carbon steel	Condensate evaporation via corrosion-resistant coil in AISI 316 low carbon steel	Condensate evaporation via corrosion-resistant coil in AISI 316 low carbon steel	Condensate evaporation via corrosion-resistant coil in AISI 316 low carbon steel
Humidity	%	-	-	-	-	-
Condensation		AIR	AIR	AIR	AIR	AIR
Cooling capacity	W	520	568	520	568	872
Supply voltage	Volt	AC230V 1N+T 50Hz				