



conforme
alla norma
EN 453
rev. 2015

INDUSTRY 4.0



CONFECTIONERY DEPOSITORS

Machine for the production of casting biscuits complete with nozzle turning device and wire cutting device for extruded biscuits.
Automatic conveyor height adjustment.

Standard Features

- Aluminum frame and stainless steel covering
- 200 programs can be stored with PLC via 7" color touch screen
- Programs with preset values
- Variable speed stainless steel dosing rollers (inverter)
- Trays width 400/460 - 600/660
- Electronically controlled bidirectional tray advancement with adjustable speed (inverter)
- Aluminum head with quick release for mold replacement (no key required)
- Variable speed nozzle rotation (inverter)
- Variable speed motorized wire/syringe cutting device (inverter)
- Steel/aluminium wire cutting bow with 6 outlets.
- Automatic Start
- Automatic table lowering
- Automatic conveyor height adjustment.
- Barriers, photocells and Reer safety plc
- Connectable



Optional

- KIT 4.0 (NOT compatible with Esmach cloud)

MODELLO/ MODEL	LARGHEZZA TEGLIA TRAY WIDTH	DIMENSIONI/ SIZE	PESO KG	POTENZA POWER	VOLTAGGIO VOLTAGE
CO 400	400-460 mm	1000x1350x1460h	295	1.85 Kw	230/400*3*T*N 50/60
CO 600	600-660 mm	1200x1350x1460h	306	1.85 Kw	230/400*3*T*N 50/60

Removable 400mm food grade anodized aluminum roller head complete with:

- Straight hopper in Aisi 304 (inclined optional)
- Extrusion rollers in Aisi 304
- Bushings in plastic material
- Knobs in Aisi 304
- Quick release for replacing the mold holder bars (no key required).



Revolving mold with 6 exits composed of:

- food-grade anodized aluminum dovetail
 - material sliding bushings plastic
 - nozzle holder gears in Aisi 304
- removable for sanitization



6 smooth centered spouts in Aisi 304 ø 10 mm

6 centered ridged nozzles in Aisi 304 ø 10 mm 10 tips



6 off-centre spouts in smooth plastic material ø 7/8 mm

6 off-center nozzles in ridged plastic material ø 7/8 mm



Wire cutting mold with 6 outlets in food-grade anodized aluminum complete with standard choice of escutcheons in plastic material (maximum Ø 50 mm round mold)



6 nozzle extensions



6-way wire cutting bow with aluminum arms.

Manual wire tensioner for quick replacement of the wire in case of breakage.



400 cm tray extension on entry

